



(800) 513-9373 • (910) 342-0445 • Fax: (910) 342-0447
P. O. Box 1259 • Wilmington, NC 28402
CPS HALF ROUND FRAMELESS DUMP

Weight:	Approximately 15,540 lbs. +/- 3%.
Length:	34'
Sides:	54"
Body:	1/4" AR400 steel (145 KSI Brinell hardness)
Nose & Gate:	3/16" AR400 steel (145 KSI Brinell hardness)
Top Rail:	12" x 4" x 1/4" High strength steel with integrated top angle.
Longitudinal:	8" x 8" x 1/4" High strength steel.
Body Braces:	1/4" High strength steel internally stiffened.
Draft Arms:	5" x 3" x 3/16" steel tube with drop legs.
Hoist:	8" 5 Stage inverted trunnion mount.
Suspension:	Hutch H900 single point suspension, keeps all eight tires on the ground.
Axles:	(2) 25,000 lb. 5" tubular with 16 1/2" x 7" cam brakes.
ABS Brakes:	ABS brakes on one axle 2 sensors and modulator valve.
Wheels:	8.25 x 22.5 steel disc (8)
Tires:	11R22.5 Michelin XZE radials (8)
Tailgate:	Air operated high lift gate gives 87" of clearance. Bracing 5 3/4" x 3 3/4" x 3/16" High strength steel mudflaps integrated "over the center" locks. Electric over air gate control.
Ladders:	Front and rear.
Fenders:	Rear bolt on.
Wire Harness:	Custom fit and fully sealed.
Paint:	Valspar urethane paint and epoxy primer (white)
Tarp:	No tarp



(800) 513-9373 • (910) 342-0445 • Fax: (910) 342-0447
P. O. Box 1259 • Wilmington, NC 28402