



(800) 513-9373 • (910) 342-0445 • Fax: (910) 342-0447
P. O. Box 1259 • Wilmington, NC 28402

INNOVATIVE INWOODS CLOSED TOP CHIP TRAILER - IWS-43

Capacity:	2,738 cubic feet (101.4 cubic yards), water level.
Weight:	Approximately 10,625 lbs. +/- 3%.
Dimensions:	43' Length, 8' Width, 13'6" Height (based on 51" Fifth Wheel height), 28" Rear Axle location, 37" King Pin setting, 36'9" King Pin to Rear Axle, 32'2½" Landing Gear to Bumper Blade
Side Walls:	.063 stressed aluminum mill finished skins, with exterior 6061-T6 aluminum aero post on 21½" center, <u>Skins lapped inwoods style</u> and sidewall rivets on 4 1/2" centers. <u>Six (6) inwoods vents, three (3) per side.</u>
Top:	Closed top, inwoods design with <u>48" wide, and 24-gauge stainless steel chip deflector.</u>
Baffle:	<u>One mounted on inside approximately 120" back from front.</u>
Front:	90-degree front corners with interior front posts. <u>Interior lined with .063 aluminum.</u>
Floor:	.063 corrugated aluminum with wood brake strips.
Rear Door:	<u>Aluminum top hinge, 2/3 door for inwoods operation, skinned with pre-paint black skins.</u>
King Pin:	Standard SAE heat-treated, 37" setting, 51" height, <u>½" king pin plate and lifting eye</u>
Landing Gear:	<u>Holland MK-5</u> 3" heavy duty channel barcing, <u>10" cross channel foot</u> , and reinforced lugs for loaded set out. Crank on dirver's side.
Sub Frame:	Hutch 8800 fixed tandem with full-welded construction.
Cross Sills:	4" x 3.2 lb./ft., 80,000 p.s.i. high strength steel, Jr. I-Beam on 21" centers.
Bumper:	ICC chip style with <u>extended inwoods dual pipe dump blade construction for end dump operation.</u>
Suspension:	Hutch CH9700 tandem, 3-leaf high arch, heavy-duty springs, with no hop option.
Axles:	Rockwell or Dana Spicer 71 ½" Track, <u>25,000 lb capacity</u> , 5" round, Hub piloted hubs, outboard drums, auto slack adjusters, and <u>dust shields.</u>
Brakes:	16½" x 7", "Q" series, 4515 ED, non-asbestos lining, type 3030 air chambers, DOT Meritor/WABCO 2S/1M (2 sensors/ 1 modulator) ABS with release valve

Tires & Wheels: (8) 11R24.5 Bridgestone R194 radial tires. (8) 8.25 x 24.5 – 10 hole hub piloted pre-painted steel wheels.

Mud Flaps: Legal rubber.

Electrical: Truck-Lite unitized wiring harness, 12 Volt.

Lights: Legal DOT light system, standard sealed lamps.

Reflectors: Legal DOT reflective tape.

Paint: Aluminum natural, steel components sand-blasted, primed and painted Pitts Red.

F.O.B. including FET \$

This offer may be withdrawn if not accepted within 30 days. Prices do not include Highway Use Tax, Federal, State, and Local Sales Taxes unless specifically stated above. Standard specifications are subject to change without prior notice.

Acceptance of Proposal:

For: Pinnacle Trailer Sales	For: _____
By: _____	By: _____
Date: _____	Date: _____

To accept this proposal, please sign where indicated and fax or send a copy of entire proposal back to Pinnacle Trailer Sales, Inc. fax (910)-342-0447. Thank you for your consideration.